

HPLC & UHPLC

Vanquish Split Samplers

LC that takes your productivity to new heights

Vanquish LC platform benefits

- Precision and reproducibility to meet every application demand
- Widest portfolio of detection technologies
- Less maintenance, and reliable set up with Thermo Scientific™ Viper™ TQ UHPLC Fittings
- Dedicated solutions for exceptional LC-MS performance
- Powerful sample capacity extension with Thermo Scientific™ Vanquish™ Sample Hub



Sample injection for highest productivity and fastest return on investment

Thermo Scientific™ Vanquish™ HPLC and UHPLC System Split Samplers perfectly combine maximum injection precision by SmartInject technology with very high sample capacity. All fluidics are consequently optimized for the highest ruggedness and uptime, even under the toughest system pressure and eluent conditions. The innovative air stream cooling provides maximum sample integrity, even in challenging environments. The customizable gradient delay volume allows for incredibly easy method transfer. Wash solvent monitoring utilizing innovative machine learning ensures the detection of empty reservoirs to reduce the risk of out-of-specification (OOS) results caused by sample carry over due to insufficient wash. Tedious sample configuration is eliminated through automated barcode reading. Throughput and application flexibility can be doubled with two independent injections units using a Thermo Scientific™ Vanquish™ Duo UHPLC System.

- Thermo Scientific™ Vanquish™ Horizon (150 MPa) and Flex (100 MPa) UHPLC Systems: Split samplers for highest injection precision with vial bottom detection technology enabling injections from limited sample amounts without any tradeoff on durability and robustness
- Thermo Scientific™ Vanquish™ Core HPLC System: Split samplers for highest injection precision for standard, routine and highly productive HPLC applications with widest gradient delay volume adjustment capabilities for easiest method transfer
- Designed for maximum application versatility: As part of the Thermo Scientific™ Vanquish™ LC platform, including Vanquish™ Amplify UHPLC and Vanquish™ Duo UHPLC systems, the samplers support a broad range of chromatographic workflows—from reverse-phase to normal-phase separations—with stainless steel, biocompatible, or inert sample flow path options



Specifications

	Split Sampler HT	Dual Split Sampler HT	Split Sampler FT	Dual Split Sampler FT	Split Sampler CT	Split Sampler C
Injection units	1	2	1	2	1	1
Operating principle	Split loop injection					
Pressure range	5–151 MPa (50–1,517 bar, 700–22,000 psi)		2–103 MPa (20–1,034 bar, 290–15,000 psi)		2–70 MPa, (20–700 bar, 290–10, 100 psi)	
Injection volume range	Default: 0.01–25 µL, min. step = 0.01 µL Optional: 0.01–100 µL min. step = 0.01 µL, up to 250 µL or up to 1,000 µL with Multidraw option, min. step = 0.01 µL				Default: 0.01–100 µL, min. step = 0.01 µL Optional: 0.01–250 µL, up to 1,000 µL with Multidraw option, min. step = 0.01 µL	
Injection volume accuracy	Typically ±0.5% for 10 µL water				Typically ±0.5% at 50 µL and ±1% at 10 µL water	
Injection volume precision	<0.25% area RSD for 1 µL (caffeine in water) Typically <0.5% area RSD for 0.5 µL (caffeine in water)				<0.25% area RSD for 3 µL (caffeine in water) Typically <0.5% area RSD for 1 µL (caffeine in water)	
Injection linearity	$r^2 > 0.99999$ (caffeine in water)					
Injection cycle time	Down to 8 s depending on separation conditions					
Minimum sample required	2 µL at 1 µL injection volume					
Vial bottom detection technology	Yes, 2.5 µL out of 3 µL with vial bottom detection and recommended vials				No	
Carry over (UV)	<0.002% with caffeine (typically: <0.0004%)					
Needle wash (external)	1 solvent per injection unit, dip rinse and continuous rinse					
Needle wash monitoring	Yes, by innovative machine learning					
Sample compartment temperature range	4–40 °C (≥23 °C below ambient at <80% RH)					–
Sample temperature accuracy	±2 °C					–
Sample temperature stability	±1 °C					–
Dwell volume (contribution of the autosampler to the system gradient delay volume)	110 µL with 25 µL sample loop (default configuration); 83 µL with sample loop of 10 µL				255 µL with 100 µL sample loop (default configuration); 124 µL with sample loop of 10 µL	
Method transfer capability	Sampler freely tunable contribution to system gradient delay volume between inject volume to 100 µL				Sampler freely tunable contribution to system gradient delay volume between 0 to 230 µL	
Sample capacity	Any four of the following (SBS footprint): <ul style="list-style-type: none"> • 54 × 12 mm OD vials (≤1.5 mL) • 96 × 6, 7, and 8 mm OD vials (≤1.2 mL) • 16 × 15 mm OD vials (≤4 mL) • 9 × 22.5 mm OD vials (≤10 mL) • Well plates (96 and 384, deep and shallow) + capacity of 12 × 22.5 mm OD vials (≤10 mL) in the carousel					
Automation features barcode reading	Barcode reading: <ul style="list-style-type: none"> • Empty segment detection • Rack/well plate verification • Inventory management 					
Liquid handling programming	Yes	–	Yes	–	Yes	Yes
GLP	Predictive performance functions for scheduling maintenance procedures based on the actual operating and usage conditions of the sampler. All system parameters logged in the Thermo Scientific™ Chromeleon™ Chromatography Data System (CDS) Audit Trail.					

Specifications *(continued)*

	Split Sampler HT	Dual Split Sampler HT	Split Sampler FT	Dual Split Sampler FT	Split Sampler CT	Split Sampler C
Biocompatible	Yes; pH range 1.5–12, chloride concentration up to 1 mol/L				No; pH range 1–13, chloride concentration up to 0.1 mol/L	
Inert (metal-free flow path)	Yes, for Part No. VH-A14-A-03	No	Yes, for Part No. VF-A14-A-03	No		
Normal-phase compatible	No		Yes, with hardware modification by 6036.3501 Normal-Phase (NP) kit VF System.		Yes, with hardware modification by 6036.3972 Normal-Phase (NP) kit VC System.	
Wetted parts	Sample flow path: MP35N or inert-coated MP35N (for Vanquish Split Sampler FT/HT Amplify), titanium, ceramics, polyetherketone, DLC Eluent flow path: MP35N, titanium, ceramics, polyetherketone, DLC, sapphire, fluoropolymers Wash liquid flow path: silicone, PP, PE, FFPM, FFKM, polyetherketone, PA, PK, PTFE (for Split Sampler C/CT and Dual Split Sampler FT/HT), TPE				Sample flow path: SST, titanium, ceramics, DLC, polyetherketone, PE-UHM Eluent flow path: SST, titanium, sapphire, polyetherketone, PE-UHMW, ceramics, DLC	
PC connection	USB 2.0; 3-port-HUB to connect further Vanquish modules					
I/O interfaces	2 × 6 pin Mini-DIN connectors each having functionality: 1 input, 1 relay out					
Safety features	Leak detection and safe leak handling					
Dimensions (h × w × d)	290 × 420 × 620 mm (11.4 × 16.5 × 24.4 in.)					
Weight	25 kg (55.1 lbs.)	29 kg (63.9 lbs.)	25 kg (55.1 lbs.)	29 kg (63.9 lbs.)	24 kg (52.9 lbs.)	22 kg (48.5 lbs.)
Power requirements	100–240 V AC, ± 10%; 50/60 Hz; max. 525 W/550 VA					
Environmental conditions	Operation: 5–35 °C; 20–80% RH non-condensing, max. 2,000 m above sea-level, Storage: -20–45 °C max. 60% RH non-condensing					
Dimensions (h × w × d)	290 × 420 × 620 mm (11.4 × 16.5 × 24.4 in.)					
Weight	25 kg (55.1 lb)	29 kg (63.9 lbs.)	25 kg (55.1 lb)	29 kg (63.9 lbs.)	24 kg (52.9 lbs.)	22 kg (48.5 lbs.)

Vanquish rack dimensions



Specifications

	6851.1020	6851.1030	6850.1023	6850.1034	6850.1030	6850.1026
Number of positions	9	16	54	96		
Rack dimensions (h x w x d)	24.5 x 127.8 x 85.5 mm					
P1	36.9 mm	36.9 mm	7.9 mm	6.15 mm	6.15 mm	6.15 mm
P2	27 mm	18 mm	14 mm	10.5 mm	10.5 mm	10.5 mm
P3	15.75 mm	15.75 mm	9.5 mm	6.75 mm	6.75 mm	6.75 mm
P4	27 mm	18 mm	13.3 mm	10 mm	10 mm	10 mm
ØD	23 mm	15.3 mm	12.15 mm	8.5 mm	7.5 mm	6 mm
Supported vial OD	22.5 mm	15 mm	12 mm	8 mm	7 mm	6 mm
Supported vial height	46.5 mm	47.5 mm	34.5 mm	41.5 mm	41.5 mm	33 mm

Ordering information

Description	Part number				
Split Sampler HT	VH-A10-A-03				
Split Sampler HT Amplify	VH-A14-A-03				
Dual Split Sampler HT	VH-A40-A-03				
Split Sampler FT	VF-A10-A-03				
Split Sampler FT Amplify	VF-A14-A-03				
Dual Split Sampler FT	VF-A40-A-03				
Split Sampler CT	VC-A12-A-02				
Split Sampler C	VC-A13-A-02				
Extension module					
Sample hub	VH-A91-A-01				
Shelf, 20 levels for shallow well plates	6910.2010				
Shelf, 9 levels for deep well plates and sample racks	6910.2020				
	Part number	Split Sampler HT/FT	Dual Split Sampler HT/FT	Split Sampler HT/FT Amplify	Split Sampler CT/C
Sample loop, 10 µL, MP35N, left	6850.1915	x	x		
Sample loop, 10 µL, inert	6852.1915			x	
Sample loop, 10 µL, MP35N, right	6850.1919		x		
Sample loop, 25 µL, MP35N, left (default)	6850.1911	x	x		
Sample loop, 25 µL, MP35N, right (default)	6850.1917		x		
Sample loop, 25 µL, inert (default)	6852.1911			x	
Sample loop, 100 µL, MP35N, left	6850.1913	x	x		
Sample loop, 100 µL, MP35N, right	6850.1918		x		
Sample loop, 100 µL, inert, left	6852.1913			x	
Sample loop, 250 µL, MP35N, left	6850.1970	x	x		
Sample loop, 250 µL, MP35N, right	6850.1975		x		
Sample loop, 1,000 µL, MP35N, left	6850.1980	x	x		
Sample loop, 1,000 µL, MP35N, right	6850.1985		x		
Sample loop, 10 µL, SST	6851.1960				x
Sample loop, 25 µL, SST	6851.1940				x
Sample loop, 100 µL, SST (default)	6851.1950				x
Sample loop, 250 µL, SST	6851.1970				x
Sample loop, 1000 µL, SST	6851.1980				x
Sample rack, 9 pos, 22.5 mm OD vials	6851.1020	x	x	x	x
Sample rack, 16 pos, 15 mm OD vials	6851.1030	x	x	x	x
Sample rack, 54 pos, 12 mm OD vials	6850.1023	x	x	x	x
Sample rack, 96 pos, 6 mm OD vials	6850.1026	x	x	x	x
Sample rack, 96 pos, 7 mm OD vials	6850.1030	x	x	x	x
Sample rack, 96 pos, 8 mm OD vials	6850.1034	x	x	x	x
Normal-Phase (NP) kit VC system	6036.3972				x
Normal-Phase (NP) kit VF system	6036.3501	x (FT only)	x (FT only)	x (FT only)	

 Click [here](#) for more information about Vanquish Split Samplers.

 Learn more at thermofisher.com/HPLC

For Research Use Only. Not for use in diagnostic procedures. © 2026 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. This information is presented as an example of the capabilities of Thermo Fisher Scientific Inc. products. It is not intended to encourage use of these products in any manners that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details. **PS73319-EN0426**