SAFETY DATA SHEET



Dimethylformamide

Section 1. Identification

GHS product identifier : Dimethylformamide

Chemical name : N,N-dimethylformamide

Other means of identification : dimethyl formamide; Formamide, N,N-dimethyl-; Dimethyl formamide-Formamide, N,N-

dimethyl-; Dimethylformamide; DMF

Product type : Liquid.

Product code : TS-20672 0020673 0020673A 0020673B 1801790 1854480 1860099 1871020 1871030

1889621 1890261 1890513 1890550 NCI1020 NCI1030

SDS# : 3759 **Chemical formula** : C3-H7-N-O **CAS**# : 68-12-2

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Supplier's details : Thermo Fisher Scientific

Pierce Biotechnology

P.O. Box 117 Rockford, IL 61105 United States 815.968.0747 or 800.874.3723

7 AM - 5 PM Central Time (GMT -06:00)

Emergency telephone number (with hours of

operation)

: CHEMTREC: 800.424.9300 Outside US: 703.527.3887

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : FLAMMABLE LIQUIDS - Category 3 substance or mixture : ACUTE TOXICITY: SKIN - Category 4

ACUTE TOXICITY: INHALATION - Category 4

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION [Unborn child] - Category 1B

GHS label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : Flammable liquid and vapor.

Harmful in contact with skin or if inhaled.

Causes serious eye irritation. May damage the unborn child.

Precautionary statements

Section 2. Hazards identification

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

Response

: IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Substance

Chemical name

: N,N-dimethylformamide

Other means of identification

: dimethyl formamide; Formamide, N,N-dimethyl-; Dimethyl formamide-Formamide, N,N-dimethyl-; Dimethyl formamide; DNF

dimethyl-; Dimethylformamide; DMF

CAS number/other identifiers

CAS number : 68-12-2

Ingredient name	%	CAS number
N,N-dimethylformamide	98 - 100	68-12-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 2/13

Section 4. First aid measures

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled. Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact: Harmful in contact with skin.

Ingestion : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 3/13

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use dry chemical, CO2, water spray (fog) or foam.

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Remark

 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Some may polymerize (P) explosively when heated or involved in a fire.

Runoff to sewer may create fire hazard. Many liquids are lighter than water.

Remark

: Vapors may form explosive mixtures with air.

Vapor explosion hazard indoors, outdoors or in sewers.

Some may polymerize (P) explosively when heated or involved in a fire.

Runoff to sewer may create explosion hazard. Containers may explode when heated.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 4/13

Section 6. Accidental release measures

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 20 to 25°C (68 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
N,N-dimethylformamide	ACGIH (United States). Absorbed through
•	skin.
	TWA: 10 ppm
	NIOSH (United States). Absorbed through
	skin.
	TWA: 10 ppm
	MSHA (United States). Absorbed through
	skin.
	TWA: 30 mg/m³
	ACGIH TLV (United States, 6/2013).
	Absorbed through skin.
	TWA: 30 mg/m³ 8 hours.
	TWA: 10 ppm 8 hours.
	NIOSH REL (United States, 4/2013).
	Absorbed through skin.
	TWA: 30 mg/m³ 10 hours.
	TWA: 10 ppm 10 hours.
	OSHA PEL (United States, 2/2013).
	Absorbed through skin.

Section 8. Exposure controls/personal protection

TWA: 30 mg/m³ 8 hours. TWA: 10 ppm 8 hours.

OSHA PEL 1989 (United States, 3/1989).

Absorbed through skin. TWA: 30 mg/m³ 8 hours. TWA: 10 ppm 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [COLORLESS TO VERY SLIGHTLY YELLOW LIQUID WITH A FAINT

AMMONIA-LIKE ODOR. STABLE UNDER NORMAL LAB CONDITIONS.]

Color : Colorless. Yellowish. Yellow. [Light]
Odor : Characteristic. Amine-like. [Slight]

Odor threshold : 100 ppm

PH : 6.7 **Melting point** : -61°C (-77.8°F)

Date of issue/Date of revision: 11/8/2013.Date of previous issue: No previous validation.Version: 16/13

Section 9. Physical and chemical properties

Boiling point : 153°C (307.4°F)

Flash point : Closed cup: 58°C (136.4°F)

Burning time : Not applicable.
Burning rate : Not applicable.

Evaporation rate : 0.2 (butyl acetate = 1)

Flammability (solid, gas) : Extremely flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge and heat.

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Some may polymerize (P) explosively when heated or involved in a fire.

Runoff to sewer may create fire hazard. Many liquids are lighter than water.

Lower and upper explosive

(flammable) limits

: Lower: 2.2% Upper: 15.2%

Vapor pressure : 0.36 kPa (2.7 mm Hg) [room temperature]

Vapor density : 2.5 [Air = 1]

Relative density : 0.95

Solubility : Soluble in the following materials: cold water, hot water, methanol, diethyl ether and

acetone.

Solubility in water : Not available.

Partition coefficient: n-

octanol/water

: -1.01

Auto-ignition temperature : 445°C (833°F)

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not available.

Aerosol product

Heat of combustion : -26.24 kJ/g

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow

vapor to accumulate in low or confined areas.

Incompatible materials: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Date of issue/Date of revision: 11/8/2013.Date of previous issue: No previous validation.Version: 17/13

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
N,N-dimethylformamide	LC50 Inhalation Vapor LC50 Inhalation Vapor	Rat Rat	3421 ppm 1948 ppm	1 hours 4 hours
	LD50 Dermal		4720 mg/kg	-
	LD50 Oral	Rat	2000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
N,N-dimethylformamide	Eyes - Severe irritant Skin - Mild irritant	Rabbit Human	-	100 Percent 24 hours 100 Percent	-

Sensitization

Not available.

Mutagenicity

Not available.

Conclusion/Summary

: Laboratory experiments have shown mutagenic effects.

Carcinogenicity

Not available.

Conclusion/Summary

: Fetotoxic in animals.

Classification

Product/ingredient name	OSHA	IARC	NTP
N,N-dimethylformamide	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled. Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact: Harmful in contact with skin.

Ingestion : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Date of issue/Date of revision: 11/8/2013.Date of previous issue: No previous validation.Version: 1

Section 11. Toxicological information

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Exposure can cause stomach pains, vomiting and diarrhea. May cause allergic skin

reactions with repeated exposure. Over-exposure may cause serious liver disorders. Can

cause gastrointestinal disturbances. Can cause central nervous system (CNS)

depression.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.

Teratogenicity: May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
			2 days 48 hours
	· ·	, ,	96 hours 21 days

Persistence and degradability

Not available.

Bioaccumulative potential

Date of issue/Date of revision	: 11/8/2013.	Date of previous issue	: No previous validation.	Version	: 1	9/13
--------------------------------	--------------	------------------------	---------------------------	---------	-----	------

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
N,N-dimethylformamide	-1.01	0.3 to 1.2	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IATA
UN number	UN2265	UN2265
UN proper shipping name	N,N-DIMETHYLFORMAMIDE	N,N-DIMETHYLFORMAMIDE
Transport hazard class(es)	3	3
Packing group	III	III
Environmental hazards	No.	No.
Additional information	Reportable quantity 100 lbs / 45.4 kg [12.698 gal / 48.068 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 60 L Cargo aircraft	Passenger and Cargo Aircraft Quantity limitation: 60 L Cargo Aircraft Only Quantity limitation: 220 L Limited Quantities - Passenger Aircraft Quantity limitation: 10 L

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 10/13

Section 14. Transport information

Quantity limitation: 220 L

Special provisions
B1, IB3, T2, TP2

Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): This material is listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA Liet II Chemicale

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name		hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
N,N-dimethylformamide	98 - 100	Yes.	No.	No.	Yes.	Yes.

SARA 313

	Product name	CAS number	%	
Form R - Reporting requirements	N,N-dimethylformamide	68-12-2	98 - 100	
Supplier notification	N,N-dimethylformamide	68-12-2	98 - 100	

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : This material is listed.

New York : This material is listed.

Section 15. Regulatory information

New Jersey : This material is listed.

Pennsylvania : This material is listed.

Canada inventory : This material is listed or exempted.

International regulations

International lists : Australia inventory (AICS): This material is listed or exempted.

China inventory (IECSC): This material is listed or exempted.

Japan inventory: This material is listed or exempted. **Korea inventory**: This material is listed or exempted.

Malaysia Inventory (EHS Register): This material is listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted.

Philippines inventory (PICCS): This material is listed or exempted.

Taiwan inventory (CSNN): Not determined.

Chemical Weapons

Convention List Schedule I

Chemicals

Chemical Weapons

Convention List Schedule

II Chemicals

Chemical Weapons

Convention List Schedule

III Chemicals

Not listed

: Not listed

: Not listed

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health 2
Chronic Health Hazard *
Flammability 2
Physical hazards 0

National Fire Protection Association (U.S.A.)

Health2Flammability2Instability/Reactivity0

Special

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of printing : 1/3/2014.

Date of issue/Date of : 11/8/2013.

revision

Date of previous issue : No previous validation.

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 12/13

Section 16. Other information

Version : 1

Prepared by : MSDS (Regulatory Specialist)

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 11/8/2013. Date of previous issue : No previous validation. Version : 1 13/13